

AMENDMENTS TO THE CLAIMS

1. (currently amended) A wireless telephone device comprising:

a transceiver for transmitting and receiving wireless signals;

a control circuit for determining when said wireless telephone device is at a location where a call forwarding operation should occur;

said control circuit automatically operating said transceiver to initiate a connection between said telephone device and a service provider when said telephone device is at said location and instructing said service provider to enable a call forwarding operation, said control circuit further operating said transceiver to send a forwarding number to said service provider,

wherein said location is a location of a power source for said wireless device,
and

wherein a user of the device is allowed to change the call forwarding number
after the device has been connected to the power source.

2. (currently amended) A wireless telephone device as in claim 1 wherein ~~said location is a location of a power source for said wireless device,~~ said wireless device further comprising at least one port for connecting with said power source, said control circuit determining when said wireless device is at said location by determining if said at least one port is connected with said power source.

3. (original) A wireless telephone device as in claim 2 wherein said power source is a battery charger.

4. (original) A wireless device as in claim 2 wherein said control circuit receives through said port said forwarding number which is stored at said power source.

5. (original) A wireless device as in claim 2, wherein said power source has an associated identification number, said wireless device further comprising a memory for storing at least one forwarding number in respective association with at least one a power source identification number, wherein said control circuit receives identification information from said power source and selects a forwarding number from said memory which is associated with said received identification information for sending to said service provider.

6. (canceled)

7. (original) A wireless telephone device as in claim 4 wherein said control circuit is operative to cause a forwarding number entered at said wireless device to be stored at said power source.

8. (original) A wireless telephone device as in claim 1 wherein said control circuit determines when said wireless telephone device is no longer at said location and in response initiates a connection between said wireless device and said service provider, and instructs said service provider to disable said call forwarding operation.

9. (canceled)

10. (currently amended) A method of operating a wireless telephone device comprising:

determining when said wireless telephone device is at a location where a call forwarding operation should occur;

automatically establishing a connection to a service provider in response to said determination, and during said connection:

instructing said service provider to initiate a call forwarding operation; and

sending a forwarding number to said service provider,

wherein said location is a location of a power source for said wireless device,

and

wherein a user of the device is allowed to change the call forwarding number after the device has been connected to the power source.

11. (canceled)

12. (original) A method as in claim 11 wherein said determination is made when said wireless device is connected to said power source.

13. (original) A method as in claim 12 wherein said power source is a battery charger.

14. (original) A method as in claim 12 further comprising receiving said sent forwarding number from said power source.

15. (original) A method as in claim 12 further comprising:

storing a plurality of forwarding numbers in respective association with a power source identification information;

determining an identification number of a power source connected to said wireless telephone device; and

selecting as said sent forwarding number a stored forwarding number associated with said determined identification information.

16. (canceled)

17. (original) A method as in claim 14 further comprising storing a forwarding number in said storage area of said power source.

18. (original) A method as in claim 10 further comprising:

determining when said wireless telephone device is no longer at said location and in response automatically initiating a connection between said wireless device and said service provider and instructing said service provider to disable said call forwarding operation.

Claims 19-20 (canceled)

21. (currently amended) A wireless telephone device comprising:

a transceiver for transmitting and receiving wireless signals;

a control circuit for determining when said wireless telephone device is at a location where a call forwarding operation should occur, said control circuit automatically operating said transceiver to initiate a connection between said telephone device and a service provider when said telephone device is at said location and instructing said service provider to enable a call forwarding operation, said control circuit further operating said transceiver to send a forwarding number to said service provider;

a plurality of ports for connection with a power source, wherein said location is a location of said power source, said control circuit determining when said wireless device is at said location by determining if one of said plurality of ports is connected with said power source; and

a memory for storing a plurality of forwarding numbers in respective association with said plurality of ports, said control circuit selecting a forwarding number in accordance with a port which is connected to said power source and causing said selecting forwarding number to be sent to said service provider,

wherein a user of the device is allowed to change the call forwarding number after the device has been connected to the power source.

22. (canceled)

23. (currently amended) A method of operating a wireless telephone device comprising:

determining when said wireless telephone device is at a location where a call forwarding operation should occur, wherein said location is a power source for said wireless device and said determination is made when said wireless device is connected to said power source, wherein said wireless telephone device has a plurality of connection ports for connection with said power source;

storing a plurality of forwarding numbers in respective association with said plurality of connection ports;

selecting as a forwarding number a stored forwarding number which is associated with a port to which said power source is connected;

automatically establishing a connection to a service provider in response to said determination, and during said connection:

instructing said service provider to initiate a call forwarding operation; and

sending said forwarding number to said service provider,

wherein a user of the device is allowed to change the call forwarding number after the device has been connected to the power source.

Claims 24-25 (canceled)